

SINGLE STAGE TRUCK JACKS

FEATURES

- A choice of three handle angles:
 - 90° for space saving storage
 - 45° for easy carrying movement
 - 0° for access to lifting point
- Heat-treated extension screw allows low pick-up height adjustment and maximum lift height
- A built-in by-pass device protects hydraulic system from over pumping damage
- Large steel wheels for easy positioning and smooth motion
- Sturdy one piece handle assembly is standard on all Blackhawk truck jacks
- User friendly, self-returning spring minimizes operators effort, greatly reducing fatigue
- In-line air filter traps contaminants and protects air motor for longer life
- Chrome plated rams
- High speed Air Turbo Motor is equipped to raise the load to the desired height efficiently, effortlessly, and safely
- U.S. Patents 5,946,912 and 6,012,377



Standard 1" and 2-1/2" adapter included (for BH6221 only)



BH6221

BH6301

| Model | Capacity | Minimum Height | Maximum Height with adapter | Extension Screw | Handle Length | Jack Size (L X W) | G.W. |
|--------|----------|----------------|-----------------------------|-----------------|---------------|-------------------|----------|
| BH6221 | 22 Ton | 9-3/4" | 22-5/8" | 3-7/8" | 47-3/8" | 22" X 12-5/8" | 100 Lbs. |
| BH6222 | 22 Ton | 8-1/2" | 22" | | 40-7/8" | 21-1/2" X 12-1/2" | 95Lbs. |
| BH6301 | 30 Ton | 11" | 18" | N/A | | | |