

# HW93690

## 10 Ton Air Operated End Lift

- Three-way heavy duty brass air valve provides fine control when lifting or lowering a vehicle
- Safety latch design provides six different automatic safety lock positions to prevent unintentional lowering of load
- Heavy duty wide base for stability and strength
- Two front swivel caster wheels and two 12" diameter semi-pneumatic rear tires provide easy maneuvering
- Adjustable lifting arm can be extended to desired position

Made in **USA** \*\*\*



HW93690

Made in **USA** \*\*\*

# HW93696A

## 2-1/2 Ton Air Operated End Lift

- Three-way heavy duty brass air valve provides fine control when lifting or aign provides five different automatic safety lock positions to prevent unintentional lowering of load
- Front swivel caster wheel and two 8" diameter rear tires provide easy maneuvering
- Adjustable lifting arm can be extended to desired position



HW93696A

END LIFTS

Model	Capacity	Minimum Height	Maximum Height	Power Raise	Saddle Spread	Min. Air Pressure For Rated Load	Distance (Lifting to Front of Saddle)	G.W.
HW93690	10 Ton	12-1/2"	50-1/2"	28"	25" - 53"	200 PSI	13"	670 Lbs.
HW93696A	2-1/2 Ton	8"	35-3/8"	24-1/2"	23-1/4" - 41-1/4"		19"	210 Lbs.