



AIR ACTUATED BOTTLE JACKS

- Effortless air operation will greatly reduce operator fatigue and speed up the efficiency of garage work
- A compact yet powerful Air Turbo Motor U.S. Patent No. 5,341,723 is equipped to raise the load to the desired height efficiently, effortlessly, and safely
- U.S. Patent No. 5,946,912, a built-in by-pass device protects hydraulic system from over pumping damage
- Versatile "Quick Connector" design provides for easy removal of air hose from air motor allowing compact storage or remote operation
- All air bottle jacks have chrome plated rams



18502
50 Ton Capacity



18992
100 Ton Capacity



18209
20 Ton Capacity



18205
20 Ton Capacity



18302C
30 Ton Capacity

Use
Standard Shop Air!
[110-175 PSI pressure]



18125
12 Ton Capacity



18122C
12 Ton Capacity



18202C
20 Ton Capacity

18122C & 18202C
are made with welded
construction which
eliminates contaminants
from entering hydraulic
system and provides
leak free operation.

Model	Capacity	Minimum Height	Maximum Height	Hydraulic Lifting	Extension. Screw	Base Size Length	Base Size Width	G.W.
18122C	12 Ton	9-1/2"	18-1/2"	5-1/2"	3-1/2"	8"	6-1/2"	31 Lbs.
18125			18-5/8"	6"	3-1/8"	8-7/8"	5-3/4"	29 Lbs.
18202C	20 Ton	9-3/4"	18-3/4"	5-1/8"	3-7/8"	8-1/2"	7-1/4"	40 Lbs.
18205		9-1/2"	18-1/4"	5-5/8"	3-1/8"	9-1/4"	6-3/4"	39 Lbs.
18209		8-1/8"	15-1/2"	4"	3-3/8"	8-1/2"	7-1/4"	35 Lbs.
18302C	30 Ton	11"	18-1/8"	7-1/8"	N/A	10-1/4"	8-1/4"	63 Lbs.
18502	50 Ton	12"	19"	7"		10-7/8"	7-3/8"	139 Lbs.
18992	100 Ton	12"	18-1/8"	6-1/8"		12-5/8"	9-3/8"	218 Lbs.