



# DUAL STAGE TRUCK JACKS

Fingertip remote control  
for added safety

- Compact, low profile design for maximum access, which fits easily and safely between wheels of tandem axle vehicle
- A built-in by-pass device protects hydraulic system from over pumping damage, U.S. Patent No.5,946,912
- High speed Air Turbo Motor is equipped to raise the load to the desired height efficiently, effortlessly and safely, U.S. Patent No. 5,341,723
- Large steel wheels for easy positioning and smooth motion
- Sturdy one piece handle assembly is standard on all Omega Truck Jacks
- The release valve at the top of the handle allows for easy height adjustment safely away from the load

Use  
Standard Shop Air!  
[110-175 PSI pressure]

Two 2-3/4" Adapters  
Standard on 23401

Use  
Standard Shop Air!  
[110-175 PSI pressure]

23227

Double Ram Model

35 Ton Capacity on the first ram  
22 Ton Capacity on the second ram

23401

Double Ram Long Chassis

40 Ton Capacity on the first ram  
20 Ton Capacity on the second ram

Model	Capacity	Minimum Height	Maximum Height with Adapter	Extension Screw	Handle Length	Jack Size (L X W)	G.W.
23227	35/22 Ton	8-1/4"	19-5/8"	3-1/4"	40-7/8"	21-5/8" X 13-7/8"	105 Lbs.
23401	40/20 Ton	7-1/4"	20-1/8"	N/A	51-1/8"	86-1/4" X 10-1/4"	149 Lbs.

1-800-992-1478