



SINGLE STAGE TRUCK JACKS

- A choice of three handle angles:
 - 90° for space saving storage
 - 45° for easy carrying movement
 - 0° for access to lifting point
- Heat treated extension screw allows low pick-up height adjustment and maximum lift height
- A built-in by-pass device protects hydraulic system from over pumping damage, U.S. Patent No.5,946,912
- Large steel wheels for easy positioning and smooth motion
- Sturdy one piece handle assembly is standard on all Omega Truck Jacks
- User friendly, self-returning spring minimizes operators effort, greatly reducing fatigue
- In-line air filter traps contaminants and protects air motor for longer life
- Chrome plated rams
- High speed Air Turbo Motor is equipped to raise the load to the desired height efficiently, effortlessly and safely, U.S. Patent No. 5,341,723

FAST & SAFE!

Effortlessly raises the saddle quickly, then power lifts to desired height.

1", 2-1/2" and 5" Adapters Standard on 23222

Fingertip remote control for added safety

1" and 2-1/2" Adapters Standard on 23221

23222
22 Ton Capacity
with extension screw

23221
22 Ton Capacity
with extension screw

23301
30 Ton Capacity

Use
Standard Shop Air!
[110-175 PSI pressure]

Model	Capacity	Minimum Height	Maximum Height with adapter	Extension Screw	Handle Length	Jack Size (L X W)	G.W.
23221	22 Ton	9-7/8"	22"	3-7/8"	48-3/4"	22-7/8" X 13-3/4"	96 Lbs.
23222		8-1/4"	21-7/8"			21-7/8" X 12-3/8"	99 Lbs.
23301	30 Ton	11"	18"	N/A		22-7/8" X 12-1/2"	100 Lbs.
23501	50 Ton	12"	19"			22-7/8" X 13-3/4"	174 Lbs.
23991	100 Ton		18-1/8"			26" X 15-3/4"	250 Lbs.