



SIDE PUMP BOTTLE JACKS



- Hydraulic system is protected from internal damage by a by-pass mechanism U.S. Patent No.5,946,912
- Machined and polished cylinders with die-cut threads provide non-abrasive leak-free, durable performance
- Fabricated from hard-cast steel with heat-treated critical stress areas
- Unique cross-type forged release valve assures positive load control
- A wide, rugged base provides stability and strength

Model	Capacity	Minimum Height	Maximum Height	Hydraulic Lifting	Extension Screw	Base Size Length	Base Size Width	G.W.
10025C	2 Ton	7-1/4"	13-5/8"	4-3/8"	2"	3-3/4"	3-5/8"	7 Lbs.
10045C	4 Ton	8"	15-3/8"	5"	2-3/8"	4"	3-7/8"	9 Lbs.
10065C	6 Ton	8-5/8"	16-3/4"	5-1/8"	3"	4-1/4"	4"	12 Lbs.
10085C	8 Ton	8-7/8"	17-5/8"	6"	2-3/4"	4-3/4"	4-3/4"	14 Lbs.
10125C	12 Ton	9-1/2"	18-5/8"	6"	3-1/8"	5-1/4"	5-1/8"	18 Lbs.
10129C		6"	10-5/8"	3"	1-5/8"			14 Lbs.
10205C	20 Ton	9-1/2"	18-5/8"	6"	3-1/8"	6-1/4"	5-7/8"	27 Lbs.
10209C		6-1/2"	11-1/4"	3-1/8"	1-5/8"			21 Lbs.
10300	30 Ton	11"	18"	7"	N/A	8-1/8"	6-7/8"	55 Lbs.
10500	50 Ton	9-1/2"	13-7/8"	4-3/4"		10-7/8"	7-5/8"	107 Lbs.

OMNI™ BOTTLE JACKS

- Hydraulic system is protected from internal damage by a by-pass mechanism U.S. Patent No.5,946,912
- Machined and polished cylinders with die-cut threads provide non-abrasive leak-free, durable performance
- Fabricated from hard-cast steel with heat-treated critical stress areas
- A wide, rugged base provides stability and strength
- Will operate at verticle or horizontal position



16123
12 Ton Capacity

16203
20 Ton Capacity



Model	Capacity	Minimum Height	Maximum Height	Hydraulic Lifting	Extension. Screw	Base Size Length	Base Size Width	G.W.
16123	12 Ton	9-1/2"	18-5/8"	6"	3-1/8"	5-1/4"	5-1/8"	18 Lbs.
16203	20 Ton					6-1/4"	5-7/8"	28 Lbs.